



Building Controls Specialist

Starlite

Home Security System



Features for STARLITE LED Keypad System Features:

Programmable Zones	8 Fully Programmable Zones
Maximum Keypad	4 Keypads**
Arming Type	Auto Home/Day/Night/Force
Real Time Arm/Disarm Timer	1 Real Time Timer (Daily/Schedule)
Real Time Clock Function	Yes
Entry/Exit Delay	Yes
Zone Types	EOL/NO/NC
Zone Sensitivity	Individual Zone Loop Response Sensitivity
Pulse Count	Yes
Zone Chime	Individual Chime Setting
Access Codes	1 Master/6 Users/1 Guests
Duress Code	Yes
Key Switch Function	Yes
Telephony Voice Interaction	Yes
Communication Method	RS 485
Remote Programming via Phone	Yes
Event Trigger & Reporting	Yes
Fast Key	Yes (Easy Menu Access)
Soft Zone	Emergency/Fire/Panic
Programming Mode	Installer/Master
CMS Reporting Format	Ademco Contact ID
Report Events	4 Phones and 4 Account Numbers
Double Call-In	Yes

Automation*

Output Control (Status Feedback)	Up to 8 IO
Real Time ON/OFF Timer	2 Pairs

Test

Walk Test
CMS Test
Siren Test
Strobe Light Test
Battery Test

Protection

Dedicated Tamper Zone
AC Power Supply Monitoring
Low Battery Indication
Telephone Line Lost Detection*
External Communication Monitoring

* Optional ** Terms and Conditions Apply

System Technical Specification

Main Panel (P/N: 2MB1-QTRNMBSETXR)
Panel Only (P/N: 2MB1-QTRNMBXXXXR)

Physical	194mm x 112mm
Electrical Voltage Input	15V DC, 2.5A
Auxiliary/Strobe Light/Bell Output	12V DC, 500mA
Siren Output	12V DC, 2A

Keypad (P/N: 2MB1-QTRNLEDKPWR)

Physical	128mm x 85mm
Electrical Voltage Input	12V DC
Electrical Current Drain	100mA



DAIKIN DAIKIN ELECTRONIC DEVICES MALAYSIA SDN. BHD.
(209388-K)

No, 2, Jalan Ragum 15/17, Seksyen 15,
40200 Shah Alam,
Selangor Darul Ehsan, Malaysia
Tel: +603 5523 1205
Website: <https://ax1smarthome.com.my/>

